

NEPTUNE CARTRIDGE FILTERS



DESIGNED AND BUILT FOR
AUSTRALIAN CONDITIONS

Neptune
for swimming pools



Simply A Better Choice!

Neptune Cartridge Filters are built to work in harsh Australian conditions. The filters are quick and easy to install and are ideal for confined spaces due to their compact and lightweight design.



PRODUCT INFORMATION

Description	Model
25 square foot Neptune Cartridge Filter	CF25
50 square foot Neptune Cartridge Filter	CF50
75 square foot Neptune Cartridge Filter	CF75
100 square foot Neptune Cartridge Filter	CF100
150 square foot Neptune Cartridge Filter	CF150
200 square foot Neptune Cartridge Filter	CF200

TECHNICAL INFORMATION

Maximum Working Pressure	250kPa / 36psi / 2.5bar		
Maximum Water Temperature	40°C		
Model	Filter Area (m ²)	Pipe Size	Max Flow Rate
CF25	2.25	1.5" / 40mm	92Lpm / 5.5m ³ / h
CF50	4.63	1.5" / 40mm	190Lpm / 11.4m ³ / h
CF75	7.00	1.5" / 40mm	283Lpm / 17.0m ³ / h
CF100	9.40	2" / 50mm	382Lpm / 22.9m ³ / h
CF150	13.72	2" / 50mm	555Lpm / 33.4m ³ / h
CF200	16.82	2" / 50mm	680Lpm / 40.9m ³ / h

KEY FEATURES

- UV resistant tank.
- Heavy duty ring-lock lid allows easy cleaning and replacement of the cartridge element.
- Screw type air bleeder for easy removal of trapped air inside the filter tank.
- High quality pressure gauge for easy inspection of the operation pressure.
- Suitable for all domestic swimming pools & spas.

PRODUCT DIMENSIONS

Model	A (mm)	B (mm)	C (mm)
CF25	445	387	225
CF50	625	567	225
CF75	805	747	225
CF100	985	927	225
CF150	1165	1107	225
CF200	1345	1287	225

CARTRIDGE FILTER ELEMENTS

Model	Element Code	D (mm)	E (mm)	Micron (µm)
CF25	RE012	Φ183	184.5	≤15
CF50	RE061	Φ183	364.5	≤15
CF75	RE126	Φ183	544.5	≤15
CF100	RE144	Φ183	724.5	≤15
CF150	RE168	Φ183	904.5	≤15
CF200	RE126 x 2	Φ183 each	544.5 each	≤15

AVAILABLE FROM YOUR
LOCAL POOL PRO STOCKIST

